

DF-W 系列联锁阀


Series locked solenoid Valves

DF3-W 系列正联锁电磁阀

Series positive locked solenoid valves



图形符号 symbols



产品特点 Features

DF3-W正联锁阀是控制压力制动器、离合器正常工作的一种专用气动元件。它保证离合器与制动器必须保持一定的结合和脱开顺序，即在压力机起动时，制动器必须首先脱开0.03秒。然后离合器才能结合；在压力机停车时，离合器必须首先脱开0.01秒，然后制动器动作。该阀反应灵敏、动作可靠。

DF3-W positively locked solenoid valve is exclusive pneumatic elements controlling the actions of the brake and clutch of a press. It ensure that clutch and brake maintain a certain procedure of gear in and release, i.e. when press starts the brake shall first release for 0.03 sec before clutch gear-in; and when the press stops, the clutch shall first release for 0.01 sec before brake active.

型号注释 Order Code


DF3 - 20/25 W

正联锁电磁阀 Positive locked solenoid valves

公称通径 Dia

公司代号 Company code

外形尺寸 Outlook & Dimension



技术参数 Specification

型号 type	DF3-20W	DF3-25W	DF3-50W	DF3-63W
参数 Item				
流量 Flow rate (m³/h)	30		63	80
有效截面积S值 Effective sectional area S valve (mm²)	190		623	787.5
联锁阀额定工作压力 Working pressure (MPa)	0.2~0.6		0.2~0.8	
电磁阀工作电压 Voltage (V)	AC:220,110,36; DC:110,24 电磁铁工作电压为额定电压的85~105%时可靠工作。 Electrilmagnet operates when its working voltage is 85~105% of nominal voltage			
联锁阀延时性能(秒) Time retardation (sec)	≥0.02			
工作温度 Working temperature (°C)	-5~50			
工作介质 Working medium	经净化并含有油雾的气体 filtered lubricated air			
联锁阀工作寿命(万次)Working life (10K times)	150			